RESTORA



RESTORA SEALER PRIMER

Data Sheet

DESCRIPTION

Restora Sealer Primer is a water based 100% acrylic sealer primer supplied as a milky white substance. When dried the solution appearance becomes a clear film.

FEATURES + BENEFITS

Water Based Easy application and easy clean up.

Good Adhesion Ensures the durability of the membrane top coat.

Fast Dry Recoat after 2 hours.

TYPICAL PROPERTIES

ColourClearApplicationBrush, Roll or Spray

Number of Coats1 minimumTip Size517Touch Dry30 minutesV.O.CLevel < 20 g/L</th>

Recoat 2 hours Volume Solids (%) 26 +/- 1% Full Cure 14 days Components 1

All figures are quoted at 25 degrees C and 50% Relative Humidity

Toxicity

Lead free. Dry film is nontoxic,

Coverage10 sqm/Ldrinking water safeClean UpWaterShelf life24 months maximum

Thinner Not Recommended Wet film per coat Recommended 100 um

Size 15 litres Dry film per coat Recommended 26 um

APPLICATION PROCESS

Refer to the top coat data sheet.

NOTE: Do not apply where rain is imminent. High humidity may effect curing times. Weather conditions must be considered and deemed suitable before proceeding with application.

HEALTH + SAFETY

- Contact Poisons Information Centre (Phone Australia: 13 11 26) or a doctor.
- Ingestion Do not induce vomiting. Give water to drink. Seek medical assistance.
- **Eye Contact** Flush eyes in eye baths until irritation subsides. Seek medical assistance.
- Skin Contact Wash thoroughly with soap and water. Launder contaminated clothing before reuse. Seek medical assistance if irritations develop.
- Inhalation Remove to rest. Seek medical assistance.
- First Aid facilities Eyebaths, safety showers
- **Medical Attention** Treat symptomatically.

RECOMMENDATIONS + PRECAUTIONS

- Ensure that appropriate workplace health and safety methods are used when working with this product.
- Use this product in a well ventilated area.
- Ensure that the surface is sound, clean and dry.
- Ensure that the application of the product is in accordance with Restora recommendations.
- Due care and consideration should be taken where water collection methods are present. Restora recommends allowing 10 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.

MSDS: Available on request. Please visit the Restora Website - www.restora.net.au

DISCLAIMER The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use on the Restora product are beyond Restora's control. Restora recommends that the applicator of this product determines the suitability of the Restora material and its recommendations prior to use or application.

Restora Coatings Pty Ltd 1300 928 826 Ph: 07 3286 4000 Fax: 07 3286 4044 Email: sales@restora.net.au