



GLOBALPOINT FLEXIBLE POINTING

Data Sheet

DESCRIPTION

Globalpoint Flexible Pointing System has been specially designed for use in construction applications, where advantage can be taken of its excellent adhesion and water resistance.

FEATURES + BENEFITS

Globalpoint Flexible Pointing:

- Fade resistant colour.
- Long service life.
- No staining by leaching cement salts.
- Waterproofing the key tile joints.
- Eliminates leaking ridges and discoloured pointing.
- Water wash up.
- 10 year guarantee from the date of purchase.

PRODUCT APPLICATION

Always ensure that the application of the Pointing is in accordance to the Globalcote recommendations.

BEDDING: Globalcote recommends that bedding cement be mixed at a 4:1 sand/cement ratio and be applied by trowel ensuring the layer is free of any holes or voids. A minimum 3mm recess of the bedding cement on the underside of the ridge is essential. Ensure this recess is clean and free of loose material.

POINTING: Ensure Globalpoint is applied to a clean, dry, dirt and dust free surface by trowel at a uniform thickness of between 3-5mm. Globalpoint should not be sponged or brushed – it is strictly a trowelable product. Always ensure weep holes are installed.

Generally Globalpoint will be water resistant after 2 hours. Do not apply where rain is imminent. Varying temperatures and high humidity may affect curing times. Weather conditions must be considered and deemed suitable before proceeding with application of the Globalcote system.

HEALTH + SAFETY

- Contact Poisons Information Centre (Phone Australia: 13 11 26) or a doctor.
- **Ingestion** Do not induce vomiting. Give water to drink. Seek medical assistance.
- **Eye Contact** Flush eyes in eye baths until irritation subsides. Seek medical assistance.
- **Skin Contact** Wash thoroughly with soap and water. Launder contaminated clothing before reuse. Seek medical assistance if irritations develop.
- **Inhalation** Remove to rest. Seek medical assistance.
- **First Aid facilities** Eyebaths, safety showers
- **Medical Attention** Treat symptomatically.

RECOMMENDATIONS + PRECAUTIONS

- Ensure that appropriate workplace health and safety methods are used when working with this product.
- Use this product in a well ventilated area.
- Ensure that the surface is sound, clean and dry.
- Ensure that the application of the product is in accordance with Globalcote recommendations.
- Due care and consideration should be taken where water collection methods are present. Globalcote recommends allowing 10 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.
- Disposal: Collect waste by sweeping or vacuuming and dispose of in accordance with local authority waste disposal directions.

MSDS: Available on request. Please visit the Globalcote Website - www.globalcote.com.au.

DISCLAIMER The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use on the Globalcote product are beyond Globalcote's control. Globalcote recommends that the applicator of this product determines the suitability of the Globalcote material and its recommendations prior to use or application.